

Powermaster®

Steam Boiler series VT3

- Vertical firetube steam boiler.
- **Designed and manufactured as per ASME.**
- Vertical high efficiency design.
- Boiler annunciator panel.
- Automatic operation, silent, superefficient, reliable and safe.
- Capacities: **5 to 60 HP.**
- Service: Dry Saturated steam.
- Fuels: **LPG and Natural gas.**
- **Long life.**



Liaison Office
Houston, Texas
1321 Upland Dr
PMB 16237
Houston, TX
77043-4718
T. (713) 999 1213

CHARACTERISTICS:

series VT3



- A Boiler annunciator panel with illuminated switches for ON/OFF; Illuminated indicators for: heat demand, flame failure, ignition, high steam pressure, low water level, second low water level, low gas pressure; Audible alarm with alarm silence button; Emergency stop button.
- B **Warrick primary LWCO.**
- C Two limit switches.
- D **Level gauge.**
- E **Gas train with double shut-off valve, pressure regulator.**
- F **Fits any gas burner.**
- G Three handholes for waterside inspection.
- H Safety relief valve.
- I **Warrick secondary LLWCO.**
- J Feedwater valves with shut-off valve and two check valves.
- K Two bottom blowdowns with **fast and slow opening valves.**